

International Bureau of WIPO
34 chemin des Colombettes
CH-1211 Geneva 20
Switzerland

Facsimile: +41 22 338 82 70 (confirmation copy by regular mail)

2 May 2006

Your ref.: PCT/NO2005/000456
Our ref.: E44705 HLA/JOB

Amendment under Art. 19 PCT
International Application No.: PCT/NO2005/000456
Applicant: Easy Well Solutions AS

Dear sirs:

Referring to the transmittal of the International Search Report and the Written Opinion dated 30 March 2006, we hereby disclose the following publications in respect of the above International Application: WO03008756 (Bosma), US 3,099,318 (Miller), US 3,918,523 (Stuber), US 4,936,386 (Colangelo), US 5,810,085 (James), US 5,048,605 (Toon), US 5,195,583 (Toon), US 5,657,822 (James), US 6,848,505 (Richard).

In our view, Bosma is the most relevant publication. Hence, and pursuant to Article 19 PCT, please find enclosed amended claims 1 – 12 intended to replace claims 1 – 6 as originally filed.

Yours faithfully
Zacco Norway AS


Hans Langan

Enclosures: Amended claims (1 – 12)

Zacco Norway AS
Haakon VII's gate 2
P.O.Box 2003 Vik
NO-0125 Oslo - Norway

Tel.: +47 22 91 04 00
Fax: +47 22 91 05 00
e-mail: info@zacco.no
www.zacco.no

Enterprise No.:
NO 982 702 887 MVA

Intellectual property rights consultants
Denmark - Norway - Sweden

AMENDED CLAIMS

5

1.

A device for expanding into a cavity (16) in a borehole (2), said cavity (16) being at least partly defined by a casting material (10) disposed in the borehole (2), characterized by an annular element (6) disposed on a tubular element (1) in the borehole and
10 comprising an expandable material capable of extending from a retracted state to an expanded state.

2.

The device of claim 1, wherein the cavity (16) is at least partly defined by the borehole
15 (2) wall.

3.

The device of claim 1, wherein the cavity (16) is at least partly defined by the tubular
20 element (1).

4.

The device of any of claims 1 – 3, wherein the cavity (16) at least partly holds a fluid.

5.

The device of claims 1 and 4, wherein the annular element (6) is adapted to extend from
25 the retracted state to the expanded state as a reaction to exposure to a fluid in the cavity (16).

6.

The device of claim 1, wherein the casting material (10) comprises hardened concrete.
30

7.

The device of claim 1, wherein the cavity (16) comprises an elongated channel
substantially defined by the casting material (10), the tubular element (1) and the
35 borehole (2) wall.

8.

A method for providing a barrier in a cavity (16) in a borehole (2), said cavity (16) being at least partly defined by a casting material (10) disposed in the borehole (2), characterized by the steps of:

- 5 - on a tubular element (1), disposing one or more annular elements (6) comprising an expandable material capable of extending from a retracted state to an expanded state;
- extending the tubular element (1) into the borehole;
- providing a casting material (10) into a first volume (12) defined by a the borehole (2) wall and the outer surface of said tubular element (1);
- 10 whereby the expandable material may extend into said cavity (16).

9.

The method of claim 8, wherein the annular elements (6) comprise a plurality of elements placed at substantially regular intervals along a length of the tubular element

15 (1).

10.

The method of claim 8, wherein the expandable element (6) is adapted to extend from the retracted state to the expanded state as a reaction to exposure to a fluid in the cavity

20 (16).

11.

The method of claim 8, wherein the expandable material extends into the cavity (16) after the casting material (10) has hardened.

25

12.

The method of claim 8, wherein the cavity (16) comprises an elongated channel substantially defined by the casting material (10), the tubular element (1) and the borehole (2) wall.

30